

Data sheet – SB M5 ST

Column drill machine



Column drill machine

Drilling technology large format
Item-No.: 205.204
EAN-No.: 4251762506088



Universal drill with infinitely variable speed drive,
depth stop with fine adjustment including
connection cable

Additional information



To the operating instructions

Technical data

Column drill machine



Drilling depth (mm)	160
Tapping performance (depending on pitch)	M30
Spindle speed infinitely variable	100 – 2.000
Spindle	MK IV
Speed display	Scale
Drilling depth indicator	Scale
Drilling depth gauge	Quick-adjust stop ring
Feed rate (mm/revolution)	manual
Table height adjustment	with rack and pinion
Motor three-phase, 400 V, pole-reversible (kW)	1,5/3,0
Continuous/Normal Drilling Capacity (mm)	35/40 (in E335/ST60)
T-slot size (arm), spacing (mm), dimension width (mm)	Number 2, 160, 14/26
Projection (mm)	300
Column diameter (mm)	125
Usable work surface (W x L) (mm)	590 x 450
Spindle/work surface distance (mm)	150 - 700
Machine dimension without packaging (mm)	610 x 850 x 1,920
Machine Dimension with Packing (mm)	637 x 1,096 x 2,120
Weight (kg)	440

Standard equipment

- ▶ Drilling depth adjustment with fine adjustment
- ▶ Emergency stop push button
- ▶ Undervoltage Trigger
- ▶ electr. Drill Protector
- ▶ Manual reversing switch for clockwise and anti-clockwise rotation
- ▶ Connection cable (1.5 m) with CEE plug
- ▶ Thermal overload protection